

FIBER WEAVE SYSTEM SPECIFICATIONS

1. **Manufacturer or Agent**
Playcare & Design Inc.
12830 Britannia Rd.
Milton, ON. L9E 0V3
www.fibertop.ca / andy@fibertop.ca
2. **Impact Surfacing**
Engineered Cedar Wood Fiber Impact Surface: Fiber Weave.
3. **Composition: Fiber Weave**
Recently harvested North American Cedar softwood comprised of virgin “off-the-log” material only.
 - a. Free of soil, leaves, twigs or other contaminants, which could hasten decomposition.
 - b. Free of any chemical treatments and/or additives.
 - c. Free of recycled wood from pallets or construction debris.
 - d. Free of tramp and heavy metals.
4. **Dimensions**
 - a. Randomly sized.
 - b. Gradation, sieve analysis, ASTM 136, cumulative passing by weight
 - 1) ¾” sieve: 99% - 100%
 - 2) 3/8” sieve: 75% - 100%
 - 3) No.16 sieve 0% - 15%
 - c. Sized to promote drainage.
5. **Properties**
 - b. Moisture absorption: maximum of 150% by weight.
 - c. Moisture content: 25% to 60% by weight.
 - d. Impact attenuation: ASTM 1292, Procedure C: 12” thickness rated to 12’.
 - e. Accessibility: tested compliant with ASTM 1951
 - f. Product quality: tested compliant with ASTM 2075-10 – Engineered Wood Fiber Standard.
6. **Compliance**
 - a. Complies with CAN/CSA-Z614
 - b. Complies with ASTM F1292, F1951-09b, F2075-10a.
7. **Installation**
 - a. Refer to system installation instructions supplied with the Fiber Weave product.
 - b. Precaution: dust or fibers may cause eye, skin & respiratory irritation. If ventilation is unavailable or inadequate during installation, use NIOSH-certified disposable or reusable particulate respirator with an efficiency rating of N95 or higher.

Note: Fiber Weave contains no controlled substances. MSDS documentation is not required for this product.